

BIO-N reader for Nexa stainless steel panel



Reference: NX3000/BIO-N
Product code: 20700016
EAN code: 8429898013855



Main characteristics

BIO-N reader assembled on special NX3000 adapter module.

- 125KHz waterproof proximity and fingerprint reader
- For stand-alone operation
- Capacity for up to 100 users per fingerprint and 900 per card
- Capacitive fingerprint sensor
- Admits PROKEY ID and TAGKEY ID cards and fobs
- Three contact output relay (C, NO and NC)
- IP66 degree of protection
- In stand-alone mode requires 12Vdc power supply

Dimensions: 100(W) x 100(H) mm

More information

Specifications	
Technology	wiegand
Type Function	Standalone, Slave
Reading / Detection Type	Proximity, Fingerprint
RFID Frequency (KHz)	125
RFID Reading /coverage distance (cm)	6
Use	Outdoor, Indoor
Max. Users	990
Mounting	Embedded
Relay contacts	Yes
Incorporates base	Yes
State LEDs	Yes
Degree of protection (IP)	66
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-25
Dimensions - High (mm)	62
Dimensions - Width (mm)	48
Dimensions - Deep (mm)	25
Weight (gr.)	342

Accessories

- PROKEY ID proximity card
- TAGKEY ID proximity key fob
- PSU-121B 12Vdc / 1.3A power supply

Visit in the website: <https://www.golmar.es/products/nx3000-bio-n>

Visit in the website: <https://www.golmar.es/products/nx3000-bio-n>