

KEYPROX SE proximity fob



Reference: KEYPROX SE
Product code: 20710016
EAN code: 3597710001573



Main characteristics

- ISO 13.56MHz key ring
- Dimensions: 35(W) x 52(H) x 10(D) mm
- Sales unit: 20

More information

Specifications	
Format	Card
Technology	MIFARE CLASSIC
ID Type	Proximity
RFID Frequency (MHz)	13.56
Serigraph	No
Customizable	No
Material	Plastic
Additional RFID specifications	Crypto-1 encryption when used in iP Opener systems
Dimensions - High (mm)	48
Dimensions - Width (mm)	35
Dimensions - Deep (mm)	7
Weight (gr.)	8

Accessories

- GM-IPOP 80D proximity, PIN and Bluetooth wall-mounted reader
- GM-IPOP 40 proximity and Bluetooth wall-mounted reader
- MR-V2 proximity reader-circuit with 2SAFE technology
- GM-SRIPOP proximity wall reader MIFARE+ for IPOP controllers
- EL4500/EASY electronic proximity module
- GM-IPOP 80 proximity and Bluetooth wall-mounted reader
- GM-IPOP CHAMP proximity reader
- GM-MRIPOP proximity wall reader MIFARE+ for IPOP controllers
- GM-ORIPOP Vandal-proof wall reader for GM-IPOP control panels
- KEYBUS SE keypad and proximity reader

Visit in the website: <https://www.golmar.es/products/keyprox-se>

Visit in the website: <https://www.golmar.es/products/keyprox-se>