

GM-IPOP CHAMP proximity reader



Reference: GM-IPOP CHAMP

Product code: 20720007

EAN code: 3760248200057



Main characteristics

- 13.56MHz proximity reader with 2SAFE technology
- For IP OPENER and EASYGATE controllers
- Suitable with CARDDOOR MF+, TAGDOOR MF+, GM-WEIPOP, ISOPROX and KEYPROX cards and keyfobs
- Status indicator light
- Embedded installation in front panels

Dimensions: 43(Ø) x 7(D) mm

Hole diameter: 25.5mm

More information

Specifications	
Technology	2SAFE
Type Function	Slave
Reading / Detection Type	Proximity
RFID Frequency (MHz)	13.56
RFID Reading /coverage distance (cm)	4
Use	Outdoor,Indoor
Mounting	Embedded
State LEDs	Yes
Input voltage	12Vdc
Powered by controller	Yes
Degree of protection (IP)	53
Maximum working temperature (°C)	70
Minimum working temperature (°C)	-20
Dimensions - Deep (mm)	7
Dimensions - Diameter (mm)	43
Dimensions - Cut-out Diameter (mm)	25.5
Weight (gr.)	60

Accessories

- 1 door access control panel GM-IPOP-1P
- 4 door access control panel GM-IPOP-4P
- CARDDOOR MF+ Mifare Plus Proximity Card
- ISOPROX proximity card
- 2 door access control panel GM-IPOP-2P
- GM-USBIPOP USB programmer for EasyGate and IP Opener controllers
- TAGDOOR MF+ Mifare Plus proximity keyfob
- GM-WEIPOP RF/Proximity Mifare transmitter control for IPOP controllers

Visit in the website: <https://www.golmar.es/products/gm-ipop-champ>

Visit in the website: <https://www.golmar.es/products/gm-ipop-champ>