

CODEPROX-N proximity and PIN reader



Reference: CODEPROX-N
Product code: 20720011
EAN code: 8429898025186



Main characteristics

- 125KHz waterproof proximity and keypad reader with Wiegand 26 technology
- For **IP OPENER Wiegand** controllers or **stand-alone operation**
- Capacity for up to 1000 users
- Admits PROKEY ID and TAGKEY ID cards and fobs
- Three contact output relay (C, NO and NC)
- Embedded installation with IP66 protection
- **Stand-alone installation requires AP-1** embedding box
- **For installation on Nexa panel, kit N3000/BIO-N (Nexa aluminium) or kit NX3000/BIO-N (Nexa stainless steel) must be acquired.**
- In stand-alone mode requires 12Vdc power supply.

Dimensions: 86(W) x 86(H) x 25(D) mm

More information

Specifications	
Technology	wiegand
Type Function	Standalone,Slave
Reading / Detection Type	PIN,Proximity
RFID Frequency (KHz)	125
RFID Reading /coverage distance (cm)	6
Use	Outdoor,Indoor
Max. Users	990
Mounting	Embedded
Relay contacts	Yes
Incorporates base	Yes
State LEDs	Yes
Input voltage	12Vdc
Powered by controller	Yes
Degree of protection (IP)	66
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-40
Dimensions - High (mm)	62
Dimensions - Width (mm)	48
Dimensions - Deep (mm)	25
Weight (gr.)	245

Accessories

- 2 door access control panel GM-IPOP-2P-WIEG
- PROKEY ID proximity card
- CODEPROX-N reader for Nexa aluminium panel
- PSU-121B 12Vdc / 1.3A power supply
- Caja de superficie SBOX-PBL para lectores BIO-N y CODEPROX-N
- 4-Door Wiegand expansion card GM-IPOP-EXP4PW
- TAGKEY ID proximity key fob
- CODEPROX-N reader for Nexa stainless steel panel
- Caja de superficie SBOX-MT para lectores BIO-N y CODEPROX-N
- Caja de empotrar AP-1

Visit in the website: <https://www.golmar.es/products/codeprox-n>

Visit in the website: <https://www.golmar.es/products/codeprox-n>