

GM-IPOP-SQ40 reader for 40x40mm informative windows




Reference: GM-IPOP-SQ40

Product code: 20720022

EAN code: 3760248203294



Main characteristics



- 13.56MHz proximity reader with 2SAFE technology.
- Integrates BLE technology that allows the user to access via smartphone (requires the purchase of "PUNTOS BLE" (BLE POINTS)). The application for its use is K-APP available on Android and IOS.
- For IP OPENER and EASYGATE controllers.
- Suitable with CARDDOOR MF +, TAGDOOR MF+, GM-WEIPOP, ISOPROX and KEYPROX cards and keyfobs.
- Installation on outdoor panels with standard 40x40mm informative windows



Promotional video "Access via Bluetooth".



Promotional video "Bluetooth Management".

Dimensions: 60(W) x 60(H) x 16(D) mm

Dimension of reading area: 40(W) x 40(H) x 2(D) mm

More information

Specifications	
Technology	2SAFE
Type Function	Slave
Reading / Detection Type	Proximity,Bluetooth
RFID Frequency (MHz)	13.56
RFID Reading /coverage distance (cm)	4
Use	Outdoor,Indoor
Mounting	Embedded
Display	No
Expandable	No
Antenna	No
Incorporates base	Yes
Incorporates cover/front panel	No
State LEDs	Yes
Input voltage	12Vdc
Powered by controller	Yes
Maximum working temperature (°C)	50
Minimum working temperature (°C)	-20
Dimensions - High (mm)	60
Dimensions - Width (mm)	60
Dimensions - Deep (mm)	16
Special dimensions (mm)	Dimensión zona de lectura: 40(An) x 40(Al) x 2(P) mm
Weight (gr.)	52

Accessories

- 1 door access control panel GM-IPOP-1P
- 4 door access control panel GM-IPOP-4P
- TAGDOOR MF+ Mifare Plus proximity keyfob
- EASYGATE controller
- 2 door access control panel GM-IPOP-2P
- CARDDOOR MF+ Mifare Plus Proximity Card
- ISOPROX proximity card

Visit in the website: <https://www.golmar.es/products/gm-ipop-sq40>

Visit in the website: <https://www.golmar.es/products/gm-ipop-sq40>