

Reference: EASYGATE-RF

Product code: 20730005

EAN code: 8429898021096



Main characteristics

EASYGATE-RF controller

- Proprietary 2SAFE protocol
- Local programming and via web environment
- 2 relay contacts
- RFID (only on relay 1) and RF verification
- Compatible with CARDDOOR MF+, TAGDOOR MF+, GM-WEIPOP, ISOPROX and KEYPROX cards and keyfobs
- Up to 2000 users (web environment) or 1500 (local mode)
- 12/24VAC or DC power supply (not included)

Dimensions: 120(W) x 100(H) x 45(D) mm

More information

Specifications	
Technology	2SAFE
No. of doors	2
Communication	Communication protocol: proprietary (2SAFE)
Reading/management type	Proximity,RF
Use	Indoor
RFID Frequency (MHz)	13.56
Requires a license	No
Format Reports	XLS
Report generation	Yes
Input voltage	12Vdc,12Vac,24Vdc,24Vac
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-20
Dimensions - High (mm)	100
Dimensions - Width (mm)	120
Dimensions - Deep (mm)	45

Accessories

- GM-IPOP 80 proximity and Bluetooth wall-mounted reader
- GM-IPOP CHAMP proximity reader
- GM-MRIPOP proximity wall reader MIFARE+ for IPOP controllers
- GM-ORIPOP Vandal-proof wall reader for GM-IPOP control panels
- GM-WEIPOP RF/Proximity Mifare transmitter control for IPOP controllers
- GM-IPOP 40 proximity and Bluetooth wall-mounted reader
- MR-V2 proximity reader-circuit with 2SAFE technology
- GM-SRIPOP proximity wall reader MIFARE+ for IPOP controllers
- GM-USBIPOP USB programmer for EasyGate and IP Opener controllers
- EL4500/EASY electronic proximity module
- TF-104 transformer

Visit in the website: <https://www.golmar.es/products/easygate-rf>

Visit in the website: <https://www.golmar.es/products/easygate-rf>