

GM-SRIPOP proximity wall reader MIFARE+ for IPOP controllers



Reference: GM-SRIPOP
Product code: 20780205
EAN code: 8429898020938



Main characteristics

- 13.56MHz proximity reader with 2SAFE technology
- For IP OPENER and EASYGATE controllers
- Compatible with CARDDOOR MF+, TAGDOOR MF+, GM-WEIPOP, ISOPROX and KEYPROX cards and keyfobs
- Status indicator light
- Indoor wall installation

Dimensions: 78(W) x 78(H) x 18(D) mm

More information

Specifications	
Technology	2SAFE
Type Function	Slave
Reading / Detection Type	Proximity
RF Frequency (MHz)	13.56
Use	Indoor
Mounting	Surface
State LEDs	Yes
Input voltage	12Vdc
Powered by controller	Yes
Dimensions - High (mm)	78
Dimensions - Width (mm)	78
Dimensions - Deep (mm)	18
Weight (gr.)	80

Accessories

- 1 door access control panel GM-IPOP-1P
- 4 door access control panel GM-IPOP-4P
- CARDDOOR MF+ Mifare Plus Proximity Card
- ISOPROX proximity card
- 2 door access control panel GM-IPOP-2P
- GM-USBIPOP USB programmer for EasyGate and IP Opener controllers
- TAGDOOR MF+ Mifare Plus proximity keyfob
- GM-WEIPOP RF/Proximity Mifare transmitter control for IPOP controllers

Visit in the website: <https://www.golmar.es/products/gm-sripop>

Visit in the website: <https://www.golmar.es/products/gm-sripop>