

PTZ-20X2AHDM 4.5" 20x dome

Reference: PTZ-20X2AHDM
 Product code: 31600233
 EAN code: 8429898019369



Main characteristics

- Compact AHD PTZ (4in1)
 4.5" metal housing
 2Mpx 1/3" Sony CMOS Sensor
 20x optical zoom (4.7mm~94mm)
 With 6 night vision LEDs
 Degree of protection IP66
 Wall bracket included
 Dimensions: Ø136 x 222mm
 Included power supply

Camera

Sensor	1/3" CMOS 2.0MP SONY323+Nextchip 2441
Output pixel	1920 H X1080 V
Lens	20X 4.7mm~94mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
S/N Ratio	≥50dB
WDR	DWDR

Dome

Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Medium rotation speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180° , Vertical 93°
Preset Points	220pcs preset(Dwell time 01-60s interval available)
A-B Scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups (Max.16 points, dwell time user selectable)
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None
Video interface output	AHD/TVI/CVI/CVBS selectable
Communication mode	RS485 (+/-) / coaxial cable
Operating Temperature	-40°C~+60°C
Power	DC12V 4A
Power Consumption	≤ 25W
Weight	N.W.:1.56KG / G.W:2.24KG

IR parameters

Auto Control IR LED	PWM
IR distance	Up to 80 meters
LEDs	6PCS Array 42Mil IR LED
Support ambient light detection	IR illumination on 1-9 grades selectable

Accessories

- CM-918 corner adapter for PTZ domes
- SP-102T ceiling bracket for 4.5" domes
- PM-919 pole adapter for PTZ domes

Visit in the website: <https://www.golmar.es/products/ptz-20x2ahdm>