

CIP-21C2W Wifi IP camera PoE for indoor use

Reference: CIP-21C2W
 Product code: 31600918
 EAN code: 8429898020112



Main characteristics

- Resolution 2Mpx
- Hybrid DVR and NVR professional compatibility
- H.264 / H.265 compression
- PIR sensor with white light
- Two-way audio
- Wide-angle lense
- Compatible with GolmarView App

Camera	
Image Sensor	1/2.7" 2Megapixel progressive CMOS
Effective Pixels	1920(H) x 1080(V)
Scanning System	Progressive
Minimum Illumination	0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)
IR Distance	up to 10m
IR On/Off Control	Auto/ Manual
IR LED	1
Warning Light	1
Lens	
Lens Type	Fixed / 2,8mm
Max. Aperture	F1.85±10%
Angle of View	H:103°
Close Focus Distance	0.2m
Video	
Compression	H.264/H.265
Streaming Capability	2 Streams
	1080P(1920x1080)/1.3M(1280x960)/
Resolution	720P(1280x720)/VGA(640 x480)/
	QVGA(320x240)
	1080P(1~25fps)
Frame Rate	VGA/QVGA(1~25fps)
Bit Rate Control	CBR/VBR
Bit Rate	H264/H265:8K ~ 8Mbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / DWDR
White Balance	Auto/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On
Smart IR	Support
Flip	Yes
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio	
Compression	G.711
Network	
Ethernet	RJ-45 (10/100Base)
Wi-Fi	2.4GHz & 5GHz Wi-Fi(IEEE802.11a/b/g/n/ac)
	10m
Protocol	
	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
	Streaming Unicast Method
	Max. User 10
	Access Users
Edge	Micro SD Card (up to 128GB)
Storage	Local PC for instant recording
Web Viewer	Yes
Smart Phone	iOS, Android
Interface	
Audio	Built-in Mic & Speaker
Interface	
Alarm	1/1,PIR
Electrical	
Power	DC12V/POE
Supply	
Environmental	
Operating	-10°C ~ +45°C (14°F ~ +113°F) / Less than 95% RH
Conditions	
Storage	-10°C ~ +45°C (14°F ~ +113°F) / Less than 95% RH
Conditions	
Construction	
Casing	Plastic
Dimensions	62 x 115 x 35 (An x Al x P) mm
Net Weight	139 g
Gross	287 g
Weight	

Visit in the website: <https://www.golmar.es/products/cip-21c2w>