

PTZ-12X5IPT dome with AUTO TRACKING system 5MPx

Reference: PTZ-12X5IPT
 Product code: 31612354
 EAN code: 8429898019451



Main characteristics

- PTZ IP Dome with Auto Tracking System
- 5Mpx resolution
- 120dB WDR System
- Intelligent video analysis
- 4.7-56.4mm (12X) autofocus lens

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	2560(H)×1920(V)
Scanning System	Progressive
Electronic Shutter	1/5-1/20000s
Min. illumination	Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)
S/N Ratio	55dB
IR Distance	Smart IR up to 80m
IR LEDs	6pcs
Lens	
Focal Length	4.7~56.4mm
Max. Aperture	F1.6~F3.0
Angle of View	H: 58.13°~6.17°, V: 35.46°~3.65°
Optical Zoom	12x
Focus Control	Auto/Manual
PTZ	
Pan/Tilt Range	Pan: 0° ~ 360° endless, Tilt: -10° ~ 90°
Manual Control Speed	Pan: 0.1° ~180° /s, Tilt: 0.1° ~90° /s
Preset Speed	Pan: 180° /s, Tilt: 90° /s
Presets	300
Intelligence	
Auto Tracking Support	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
IVS	
Video	
Compression	H.265, H.264, MJPEG
Streaming Capability	3 Streams
Stream / Frame Rate	Stream1: 2560×1920/2048×1536/1280×960 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps
Bit Rate Control	CBR/VBR
Day/Night	Auto(ICR) / Color / B/W

Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Electronic Image Stabilization(EIS)	N/A
Digital Zoom	16x
Motion Detection	Off / On
Audio	
Compression	G.711, RAM_PCM
Network	
Ethernet	RJ-45 (10/100Base-T) IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP
Protocols:	
Interoperability	ONVIF, CGI
Max. User Access	10 Users
Web Viewer	
Interface	
Ethernet	11 Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	1ch Audio In,1ch Audio Out
Alarm	2ch Alarm In,1ch Alarm Out
RS485	N/A
General	
Power Supply	DC12V/POE+
Power Consumption	Less than 25W
Operating Temperature	Starting Temperature: -40°C ~ 60°C (-40°F ~ 140 °F) Working Temperature:-55°C ~ 60°C (-67°F ~ 140 °F)
Storage Conditions	Less than 90% RH
Ingress Protection	IP66,TVS4000V
Casing	Metal
Dimensions	146.6×139.3×218.3mm
Net Weight	1.5Kg

Image BLC/HLC/WDR (120dB)
Enhancement
White
Balance Auto/Tungsten/Fluorescent/Daylight/Shadow/Manual

Visit in the website: <https://www.golmar.es/products/ptz-12x5ipt>

Golmar Sistemas de Comunicación S.A.

Silici 13 · 08940 Cornellà de Llobregat (Barcelona) · Tel: +34 934 800 696 · Fax: +34 934 742 404 · golmar@golmar.es · www.golmar.es