

CIP-24V2E vandal-resistant PoE dome IP camera, 2Mpx

Reference: CIP-24V2E
 Product code: 31691026
 EAN code: 8429898018492



Main characteristics

- Vandal-resistant dome with 2.8-12mm lens 2Mpx PoE
- 1/2.7" Progressive CMOS Sensor
- H.264 / H.265 compression
- Owner protocol / Onvif 2.6
- Varifocal lens 2.8-12mm / Field of view 120° - 57°.
- 20 leds (SMD) / 40m
- Degree of protection IP66
- Dimensions 147(Ø) x 117(P)

Resolution	2MP 1920(H)×1080(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.8-12 mm H.FOV: 120 - 57°
Day & Night	IR cut filter with auto switch
WDR	Digital WDR
Video Compression	H.265/H.264
Video bit rate	256Kbps ~ 8Mbps
Stream	Dual
	Mainstream (1~25fps)
	1080P(1920x1080), 960P(1280x960),
Frame Rate	720P(1280x720)
	Substream (1~20fps)
	VGA(640x480), QVGA(320x240)
Image Settings:	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable

Image Settings:	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
Privacy Mask	Support
Video Analytics	N/A
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP,
System Compatibility	ONVIF(Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	20pcs(SMD)
IR Range	Up to 40m
SD storage	no
Alarm Trigger	no
Audio	no
Video Output:	no
Reset Button	no
PoE	yes
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø147 X117.3mm
Weight	appr. 805g
Storage Temperature	-30 +60°C
Operating Temperature	-30 +55°C

Accessories

- C-BASE03 high base for camera

Visit in the website: <https://www.golmar.es/products/cip-24v2e>