

CIP-24D5MA dome IP camera with PoE video analysis, 5Mpx

Reference: CIP-24D5MA
 Product code: 31691030
 EAN code: 8429898018539



Main characteristics

- Dome with video analysis and motorized lense 5Mpx
 - 1/2.8" Progressive CMOS Sensor
 - 2.8-12mm motorized autofocus optics
 - Field of view 109° - 32°
 - Compression H.265 / H.264
 - Owner protocol / Onvif 2.6
 - Advanced video analysis (perimeter, crossing line, stationary object, pedestrian detection, face detection, counter)
 - 40 leds (SMD) / 40m
 - Degree of protection IP66
 - With audio terminal, reset, alarm, video output
 - Dimensions 135 (Ø) x 120(P)mm
 - Power supply 12Vcc / PoE

Resolution	5MP 2592(H)×1944(V)	Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection(DEEP LEARNING), Cross Counting.
Image Sensor	1/2.8" Progressive CMOS	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP,
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	System Compatibility	ONVIF(Ver 2.6, Profile S, Profile G)
Shutter	1/5 ~ 1/20000s	Interface	RJ45 10M / 100M Ethernet interface x1
Lens	2.8 ~ 12mm (Motorized) H.FOV: 109 ~ 32°	Led	40pcs(SMD)
F No.	F No. W:1.6--T:2.9±5%	IR Range	Up to 40m
Day & Night	IR cut filter with auto switch	SD storage	yes Micro SD/SDHC/SDXC slot, up to 128 GB
WDR	120 dB	Alarm Trigger	1 input / 1 output
Video Compression	H.265/H.264	Audio	1 input / 1 output (RCA)
Video bit rate	256Kbps ~ 12Mbps	Video Output:	yes
Triple Stream	yes	Reset Button	yes
	Mainstream default 30fps	PoE	yes
	5MP (3072x1728)(2592x1944),	Water Proof	IP 66
	4MP(2592x1520), 3MP(2304x1296)	Power Supply	DC 12V/POE
	1080P(1920x1080), 720P(1280x720),	Consumption	≤ 9W
Resolution	Substream default 30fps)	Dimension	Ø135.4 X 86mm
	720P(1280x720), VGA(640x480),	Weight	appr.
	QVGA(320x240)	Storage Temperature	-30 +60°C
	Mobilestream default 10fps	Operating Temperature	-30 +55°C
	VGA(640x480), QVGA 320x240		
Image Settings:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, Hue adjustable		
BLC	Support		
ROI	Support		

Visit in the website: <https://www.golmar.es/products/cip-24d5ma>