

Bullet IP camera CIP-24B8FA Full color 2.8-12mm motorized VA 8Mpx



Reference: CIP-24B8FA
Product code: 31691034
EAN code: 8429898026145



Main characteristics

- 1/2.7" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif (S/G/T profile)
- 2.8 to 12mm autofocus motorised lense
- 111° to 36° horizontal angle of view
- Advanced video analytics (perimeter, line of sight, pedestrian and face detection, crowd and queue detection...)
- Infrared illumination with 35m range
- White light illumination with 30m range
- IP67 protection rating
- Micro SD card slot
- Audio, reset and alarm terminals
- Power-Out function
- Compatible with C-BASE01, C-BASE02 and C-BASE05 base stations
- Dimensions: 84(Ø) x 242(D) mm

More information

Visit in the website: <https://www.golmar.es/products/cip-24b8fa>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Bullet IP camera CIP-24B8FA Full color 2.8-12mm motorized VA 8Mpx



Specifications	
Type	Bullet
Technology	IP
Image sensor	1/2,7" progressive CMOS
Max. Resolution	8Mpx
Colour	White
Mounting	Wall
Lense	Motorized
Focal length	2,8-12 mm
Zoom (x)	4
Max. Aperture ratio	F1,2
Horizontal field of view (°)	113(W) - 36(T)°
Vertical field of view (°)	59(W) - 20(T)°
Minimum illumination (lux)	Color 0.007lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON
Night vision mode	Full Color
White light distance (m)	30
IR distance max. (m)	35
Autotracking	No
WDR	No
AOC	No
Additional functions	AWB,BLC,AES,3D-DNR,D-WDR
Bitrate	256Kbps ~ 16Mbps
Main Stream (FPS)	25 fps @ 8MP(3840x2160), 5MP(2592x1944,3072x1728), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960), 720P(1280x720)
Sub Stream (FPS)	25 fps @ 720P(1280x720), VGA(640x480), QVGA(320x240)
Video compression	H.264,H.265
Face recognition	No
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Internal storage	Yes (max 256Gb)
Network interface	RJ45
Built-in microphone	No
Built-in speaker	No
UTC	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Degree of protection (IP)	67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95%
Input voltage (V)	12Vcc,PoE
Included power supply	No
Dimensions - Diameter (mm)	84
Dimensions - Deep (mm)	242
Weight (gr.)	694
Certifications	CE, RoHS

Accessories

- C-BASE01 high junction box for camera
- C-BASE02 high junction box for camera
- C-BASE05 junction box for bullet

Visit in the website: <https://www.golmar.es/products/cip-24b8fa>