

CIP-21B5E bullet PoE IP camera, 5Mpx

Reference: CIP-21B5E
 Product code: 31691053
 EAN code: 8429898018584



Main characteristics

- 1/2.7" Progressive CMOS sensor
- H.264 / H.265 compression
- Proprietary protocol / Onvif 2.6
- 2.8mm fixed optics
- 92° horizontal angle of view
- Infrared illumination with 30m range (18 SMD LEDs)
- IP66 degree of protection
- Compatible with sockets C-BASE01, C-BASE02 and C-BASE05
- Dimensions: 63(Ø) x 115(D) mm

Resolution	5MP 2592(H)×1944(V)	Image Settings:	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
Image Sensor	1/2.7" Progressive CMOS	BLC	Support
Min. Illumination	Color 0.05 lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Privacy Mask	Support
Shutter	1/5 ~ 1/20000s	Video Analytics	N/A
Slow shutter	Support	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
Lens	2.8 mm H.FOV: 92°	System Compatibility	ONVIF(Ver 2.6)
Day & Night	IR cut filter with auto switch	Interface	RJ45 10M / 100M Ethernet interface x1
WDR	Digital WDR	Led	18pcs(SMD)
Video Compression	H.265/H.264	IR Range	Up to 30m
Video bit rate	256Kbps ~ 8Mbps	SD storage	no
Stream	Dual	Alarm Trigger	no
	Mainstream (1~15fps)	Audio	no
	5MP(2592×1944),4MP(2592×1520)	Video Output:	no
Frame Rate	3MP(2048×1520),1080P(1920×1080)	Reset Button	no
	960P(1280×960), 720P(1280×720)	PoE	yes
	Substream (1~15fps)	Water Proof	IP 66
	VGA(640×480),QVGA(320×240)	Power Supply	DC 12V/POE
		Consumption	≤ 7W
		Dimension	Ø63 X115mm
		Weight	appr. 225g
		Storage Temperature	-30 +60°C
		Operating Temperature	-30 +55°C

Visit in the website: <https://www.golmar.es/products/cip-21b5e>