

CIP-24B2MA bullet IP camera with PoE video analysis, 2Mpx

Reference: CIP-24B2MA
 Product code: 31691060
 EAN code: 8429898018607



Main characteristics

- 1/2.8" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif 2.6
- 2.8 to 12mm autofocus motorized lens
- 109° to 32° horizontal angle of view
- Advanced video analytics (perimeter, cross line, pedestrian and face detection)
- Infrared illumination with 40m range
- IP66 protection rating
- Micro SD card slot
- Audio, reset, alarm and video output terminals
- Power-Out function
- Compatible with C-BASE01, C-BASE02 and C-BASE05
- Dimensions: 84(Ø) x 242(D) mm

Resolution	2MP 1920(H)×1080(V)	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
Image Sensor	1/2.8" Progressive CMOS (OV12895)	System Compatibility	ONVIF(Ver 2.6, Profile S, Profile G)
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Interface	RJ45 10M / 100M Ethernet interface x1
Shutter	1/5 ~ 1/20000s	Led	30pcs(SMD)
Lens	2.8 ~ 12mm (Motorized) H.FOV: 109 ~ 32°	IR Range	Up to 40m
F No.	F No. W:1.6--T:2.9±5%	SD storage	yes Micro SD/SDHC/SDXC slot, up to 128 GB
Day & Night	IR cut filter with auto switch	Alarm Trigger	1 input / 1 output
WDR	120 dB	Audio	1 input / 1 output (RCA)
Video Compression	H.265/H.264	Video Output:	yes
Video bit rate	256Kbps ~ 12Mbps	Reset Button	yes
Triple Stream	yes	PoE	yes
	Mainstream default 30fps	Water Proof	IP 66
	1080P(1920x1080), 720P(1280x720),	Power Supply	DC 12V/POE
	Substream default 30fps)	Consumption	≤ 9W
Resolution	1080P(1920x1080),720P(1280x720),VGA(640x480),	Dimension	Ø84 X 242mm
	QVGA(320x240)	Weight	appr. 805g
	Mobilestream default 10fps	Storage Temperature	-30 +60°C
	VGA(640x480), QVGA 320x240	Operating Temperature	-30 +55°C
Image Settings:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, Hue adjustable		
BLC	Support		
ROI	Support		
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection,Face Detection(DEEP LEARNING),Cross Counting.		

Accessories

- C-BASE01 high base for camera
- C-BASE05 sub-base for bullet
- SW-104 4-port PoE Switch
- C-BASE02 high base for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications

Visit in the website: <https://www.golmar.es/products/cip-24b2ma>