

Reference: CIP-24D2MA2  
 Product code: 31691065  
 EAN code: 8429898022758



## Main characteristics

- Dome with video analysis and motorized optics 2Mpx
- 1/2.8" Progressive CMOS Sensor
- 2.8-12mm motorized autofocus optics
- Field of view 109° - 32°
- Compression H.264 / H.265
- Owner protocol / Onvif 2.6
- Advanced video analysis (perimeter, crossing line, stationary object, pedestrian detection, face detection, counter)
- 40 leds (SMD) / 40m
- Degree of protection IP66
- With audio terminal, reset, alarm, video output
- Dimensions 135 (Ø) x 120(P)mm
- Power supply 12Vcc / PoE

Resolution	2MP 1920(H)×1080(V)	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
Image Sensor	1/2.8" Progressive CMOS (OV12895)	System Compatibility	ONVIF( Ver 2.6, Profile S, Profile G)
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Interface	RJ45 10M / 100M Ethernet interface x1
Shutter	1/5 ~ 1/20000s	Led	40pcs(SMD)
Lens	2.8 ~ 12mm (Motorized) H.FOV: 109 ~ 32°	IR Range	Up to 40m
F No.	F No. W:1.6--T:2.9±5%	SD storage	yes Micro SD/SDHC/SDXC slot, up to 128 GB
Day & Night	IR cut filter with auto switch	Alarm Trigger	1 input / 1 output
WDR	120 dB	Audio	1 input / 1 output (RCA)
Video Compression	H.264/H.265	Video Output:	yes
Video bit rate	256Kbps ~ 12Mbps	Reset Button	yes
Triple Stream	yes	PoE	yes
	Mainstream default 30fps	Water Proof	IP 66
	1080P(1920x1080), 720P(1280x720),	Power Supply	DC 12V/POE
	Substream default 30fps )	Consumption	≤ 9W
Resolution	1080P(1920x1080),720P(1280x720),VGA(640x480), QVGA(320x240)	Dimension	Ø135.4 X 86mm
	Mobilestream default 10fps	Weight	appr.
	VGA(640x480), QVGA 320x240	Storage Temperature	-30 +60°C
Image Settings:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, Hue adjustable	Operating Temperature	-30 +55°C
BLC	Support		
ROI	Support		
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection,Face Detection(DEEP LEARNING),Cross Counting.		

Visit in the website: <https://www.golmar.es/products/cip-24d2ma2>