

Bullet IP camera, CIP-124B2E PoE, 2Mpx



Reference: CIP-124B2E
Product code: 31692075
EAN code: 8429898024080



Main characteristics

- 1/2.7" Progressive CMOS sensor
- H.264 / H.265 compression
- Proprietary protocol / Onvif 2.6
- 2.8 to 12mm motorised optics
- 106° to 35° horizontal angle of view
- Infrared illumination with 40m range (4 leds)
- IP66 protection rating
- Micro SD card slot
- Audio terminals
- Compatible with C-BASE01, C-BASE02 and C-BASE05
- Dimensions: 84(Ø) x 242(D) mm

More information

Specifications	
Type	Bullet
Technology	IP
Image sensor	1/2,7" progressive CMOS
Max. Resolution	2Mpx
Images by sec. (FPS)	25
Colour	White
Mounting	Wall
Lense	Motorized
Focal length	2.8-12mm
Zoom (x)	4
Horizontal field of view (°)	106
Night vision mode	Day/Night
IR distance max. (m)	40
Additional functions	AWB,BLC,AES,3D-DNR,D-WDR
Bitrate	128Kbps ~ 4Mbps
Main Stream (FPS)	25 fps @ 1080P (1920x1080)
Sub Stream (FPS)	25 fps @ VGA (640x480)
Video compression	H.264,H.265
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	No
I / O audio	1/1
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Compatibility	C-BASE01, C-BASE-02 and C-BASE05
Degree of protection (IP)	IP66
Material	Aluminium
Input voltage (V)	12Vcc,PoE
Included power supply	No
Dimensions - Diameter (mm)	84
Dimensions - Deep (mm)	242
Certifications	CE,RoHS

Accessories

- C-BASE01 high junction box for camera
- C-BASE05 junction box for bullet
- SW-104 4-port PoE Switch
- C-BASE02 high junction box for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications

Visit in the website: <https://www.golmar.es/products/cip-124b2e>

Visit in the website: <https://www.golmar.es/products/cip-124b2e>