

# Bullet FULL COLOUR IP Camera CIP-31B2F PoE, 2Mpx

Reference: CIP-31B2F  
 Product code: 31693100  
 EAN code: 8429898024943



## Main characteristics

- 1/2.7" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif
- 3.6mm fixed optics
- 89° horizontal angle of view
- 24h colour image by default
- Visible illumination with 25m range (2 leds)
- IR illumination with 30m range (2 leds)
- Operating Modes: Full colour, day/night, programmed
- Built-in microphone
- IP66 degree of protection
- Compatible with C-BASE01, C-BASE02 and C-BASE05
- Dimensions: 69(Ø) x 151(D) mm

|                        |   |
|------------------------|---|
| Type                   | Bullet                                      |
| Technology             | IP  |
| Image sensor           | Progressive CMOS                            |
| Maximum resolution     | 2MPx  |
| Optics                 | 3.6mm                                       |
| Minimum illumination   | 0 lux IR ON                                 |
| Full Color             | Yes   |
| Day / Night            | Yes   |
| White light range      | 25m   |
| Max. infrared range    | 30m   |
| Additional features    | DWDR, 3D DNR, AGC, AWB                      |
| Bitrate                | 128Kbps ~ 4Mbps                             |
| Main Stream            | 1080P (1920x1080)                           |
| Sub Stream             | VGA (640x480)                               |
| Compression            | H.265 / H.264                               |
| Video analysis         | No  |
| Internal storage       | Yes (max. 256Gb)                            |
| Network interface      | RJ45  |
| Alarms                 | No  |
| Audio (RCA)            | No  |
| Built-in microphone    | Yes   |
| Remote access          | Web Browser, GolmarView App, VMS Pro for PC |
| Compatibility          | ONVIF                                       |
| Base compatible        | C-BASE01, C-BASE02, C-BASE05                |
| Protection rating (IP) | IP66  |
| Material               | Aluminium                                   |
| Operating temp.        | -30 +60°C ≤ 95% HR                          |
| Power consumption      | 5 W   |

|              |                      |
|--------------|----------------------|
| Power supply | 12Vdc / PoE          |
| Dimensions   | 69(Ø) x<br>151(D) mm |
| Weight       | 391 g                |

Visit in the website: <https://www.golmar.es/products/cip-31b2f>

---

**Golmar Sistemas de Comunicación S.A.**

Silici 13 · 08940 Cornellà de Llobregat (Barcelona) · Tel: +34 934 800 696 · Fax: +34 934 742 404 · [golmar@golmar.es](mailto:golmar@golmar.es) · [www.golmar.es](http://www.golmar.es)