

2Mpx bullet camera CIP-24B2E, PoE

Reference: CIP-24B2E
 Product code: 31691052
 EAN code: 8429898018577



Main characteristics

- Bullet camera with 2Mpx PoE 2.8-12mm lense
 1/2.7" Progressive CMOS Sensor
 H.264 / H.265 compression
 Owner protocol / Onvif 2.6
 Varifocal lens 2.8-12mm / FOV 120° - 57°
 30 leds (SMD) / 40m
 Degree of protection IP66
 Dimensions 77(Ø) x 240(D)mm

Additional information

Resolution	2MP 1920(H)×1080(V)	Image Settings:	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
Image Sensor	1/2.7" Progressive CMOS	BLC	Support
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Privacy Mask	Support
Shutter	1/5 ~ 1/20000s	Video Analytics	N/A
Slow shutter	Support	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
Lens	2.8-12 mm H.FOV: 120 - 57 °	System Compatibility	ONVIF(Ver 2.6)
Day & Night	IR cut filter with auto switch	Interface	RJ45 10M / 100M Ethernet interface x1
WDR	Digital WDR	Led	30pcs(SMD)
Video Compression	H.265/H.264	IR Range	Up to 40m
Video bit rate	256Kbps ~ 8Mbps	SD storage	no
Stream	Dual	Alarm Trigger	no
Frame Rate	Mainstream (1~25fps) 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substream (1~20fps) VGA(640x480),QVGA(320x240)	Audio	no
		Video Output:	no
		Reset Button	no
		PoE	yes
		Water Proof	IP 66
		Power Supply	DC 12V/POE
		Consumption	≤ 7W
		Dimension	Ø77 X240mm
		Weight	appr. g
		Storage Temperature	-30 +60°C
		Operating Temperature	-30 +55°C

Visit in the website: <https://www.golmar.es/products/2mpx-bullet-camera-cip-24b2e-poe>