

High Speed ONVIF Dome PTZ-12X5IPT with Autotracking

Reference: PTZ-12X5IPT
 Product code: 31612354
 EAN code: 8429898019451



Main characteristics

- PTZ IP Dome with Auto Tracking System
- 5Mpx resolution
- 120dB WDR System
- Intelligent video analysis
- 4.7-56.4mm (12X) autofocus lens

Additional information

| | | | |
|-----------------------|---|-------------------------------------|--|
| Camera | | Gain Control | Auto/Manual |
| Image Sensor | 1/2.8" Progressive Scan CMOS | Noise Reduction | 2D/3D DNR |
| Effective Pixels | 2560(H)×1920(V) | Electronic Image Stabilization(EIS) | N/A |
| Scanning System | Progressive | Digital Zoom | 16x |
| Electronic Shutter | 1/5-1/20000s | Motion Detection | Off / On |
| Min. illumination | Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON) | Audio | |
| S/N Ratio | 55dB | Compression | G.711, RAM_PCM |
| IR Distance | Smart IR up to 80m | Network | |
| IR LEDs | 6pcs | Ethernet | RJ-45 (10/100Base-T) |
| Lens | | Protocols: | IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP |
| Focal Length | 4.7~56.4mm | Interoperability | ONVIF, CGI |
| Max. Aperture | F1.6~F3.0 | Max. User Access | 10 Users |
| Angle of View | H: 58.13°~6.17°, V: 35.46°~3.65° | Web Viewer | <IE11 |
| Optical Zoom | 12x | Interface | |
| Focus Control | Auto/Manual | Ethernet | I1 Ethernet (10/100 Base-T) RJ-45 Connector |
| PTZ | | Audio Interface | 1ch Audio In,1ch Audio Out |
| Pan/Tilt Range | Pan: 0° ~ 360° endless, Tilt: -10° ~ 90° | Alarm | 2ch Alarm In,1ch Alarm Out |
| Manual Control Speed | Pan: 0.1° ~180° /s, Tilt: 0.1° ~90° /s | RS485 | N/A |
| Preset Speed | Pan: 180° /s, Tilt: 90° /s | General | |
| Presets | 300 | Power Supply | DC12V/POE+ |
| Intelligence | | Power Consumption | Less than 25W |
| Auto Tracking Support | Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad | Operating Temperature | Starting Temperature: -40°C ~ 60°C (-40°F ~ 140 °F) Working Temperature:-55°C ~ 60°C (-67°F ~ 140 °F) |
| IVS | | Storage Conditions | Less than 90% RH |
| Video | | Ingress Protection | IP66,TVS4000V |
| Compression | H.265, H.264, MJPEG | Casing | Metal |
| Streaming Capability | 3 Streams | Dimensions | 146.6×139.3×218.3mm |
| Stream / Frame Rate | Stream1: 2560×1920/2048×1536/1280×960 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps | Net Weight | 1.5Kg |
| Bit Rate Control | CBR/VBR | | |
| Day/Night | Auto(ICR) / Color / B/W | | |

Day/Night Auto(ICR) / Color / B/W
Image Enhancement BLC/HLC/WDR (120dB)
White Balance Auto/Tungsten/Fluorescent/Daylight/Shadow/Manual

Visit in the website: <https://www.golmar.es/products/high-speed-onvif-dome-ptz-12x5ipt-with-autotracking>

Golmar Sistemas de Comunicación S.A.

Silici 13 · 08940 Cornellà de Llobregat (Barcelona) · Tel: +34 934 800 696 · Fax: +34 934 742 404 · golmar@golmar.es · www.golmar.es