

4G2INT Wireless N Router

Reference: 4G2INT

Product code: 31600455

EAN code:



Main characteristics

- 3G/4G Wireless N Router
- 3G/4G SIM card ready
- Two detachable advanced LTE antennas

Additional information

HARDWARE FEATURES

Interface	3 LAN 10/100Mbps Ports, 1 LAN/WAN 10/100Mbps Port and 1 SIM Card Slot
Ports	3 x 10/100Mbps LAN Port, 1 x 10/100Mbps LAN/WAN Port, 1 x Micro SIM Card Slot
Buttons	WPS/Reset button, Wi-Fi On/Off button and Power On/Off button
External Power Supply(EU)	9V/0.85A
External Power Supply(APAC)	12V/1A
Dimensions	(6.85 x 4.9 x 1.32 in.) 174 x 124.5 x 33.5 mm
Antenna Type	V3/APAC: 2 4G LTE Internal Antennas V4/V2/V1: 2 external detachable 4G LTE antennas

WIRELESS FEATURES

Wireless Standards	IEEE 802.11b/g/n 2.4GHz
Frequency	2.4GHz
Signal Rate	300Mbps at 2.4GHz
Receive Sensitivity	11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm
Transmit Power	CE: <20dBm(2.4GHz)
Wireless Functions	Enable/Disable Wireless Broadcasting, WMM and Wireless Statistics
WAN Failover	Yes
Wireless Security	64/128-bit WEP, WPA/WPA2 and WPA-PSK/WPA2-PSK Encryption
Network Type	4G: FDD-LTE Cat4 (800/900/1800/2100/2600 MHz), TDD-LTE (2300/2500/2600 MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100 MHz)

SOFTWARE FEATURES

Quality of Service	WMM, QoS
Mode of Operation	3G/4G Router and Wireless Router
Management	Access Control, Local Management, Remote Management
WAN Connection Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP and DMZ
Dynamic DNS	TP-Link DDNS, DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec
Access Control	Parental Controls, Local Management Control, Host List, Access Control
Firewall Security	DoS, SPI Firewall, IP and MAC address binding
Protocols	Supports IPv4 and IPv6
Guest Network	1 Guest Network on 2.4GHz
VPN Server	PPTP VPN, OpenVPN

OTHER

Certifications	CE, FCC, RoHS
Package Contents	300Mbps Wireless N 4G LTE Router, TL-MR6400 RJ45 Ethernet Cable Power Supply Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari browser 4.0 or higher, or other Java-enabled browsers Micro SIM card
Environmental Factors	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% noncondensing

Golmar Sistemas de Comunicación S.A.

Silici 13 · 08940 Cornellà de Llobregat (Barcelona) · Tel: +34 934 800 696 · Fax: +34 934 742 404 · golmar@golmar.es · www.golmar.es